



Telescopic tri-oval hot sticks

CE-TL-series

Insulated telescopic hot sticks are essential tools for electrical utility workers, providing a protective barrier against electric shock when working on live equipment. These sticks are ideal for performing tasks from the ground under light mechanical constraints, such as disconnecting or reconnecting fuses, detecting voltage, and executing light maneuvers. The CE-TL-2 series can also be used to safely operate earthing and short-circuiting equipment, ensuring worker safety and efficient operations.

Product features

- Tested according to ASTM F 1826 (Live Line and Measuring Telescoping Tools)
- Dielectric withstand voltage: 100 kV / 30 cm (1'')
- Stick designed with composite tube made of glass-reinforced plastic (GRP) and foam-filled tip section
- Additional protection attained by sealing the inner tube to prevent water from entering
- End-fitting is a serrated universal (K)
- Tri-oval section stick optimizes ergonomics by providing better hand grip for greater handling force and higher rigidity when extended for excellent handling control
- Square-shaped button provides reinforced resistance
- Heavy duty rubber boot bottom
- Stick stopper feature prevents inadvertent section extension during transport
- Easy take-apart sections support easy maintenance plans
- Delivered with maneuver hook 11-5306-2 (*except CE-TL-2-015-K and CE-2-TL-020-K)

Product code	Folded length (mm)	Extended length (mm)	Folded length (ft)	Extended length (ft)	Weight (kg)	Weight (lbs)
CE-TL-2-015-K	900	1500	2'11"	4'11"	0.8	1.76
CE-TL-2-020-K	1140	2000	3'9"	6'7"	0.9	1.98
CE-TL-2-026-K	1450	2600	4'9"	8'6"	1.2	2.65
CE-TL-3-038-K	1500	3800	4'11"	12'6"	1.8	3.97
CE-TL-4-051-K	1550	5100	5'1"	16'9"	2.5	5.51
CE-TL-5-064-K	1600	6400	5'3"	21'0"	3.3	7.28
CE-TL-6-078-K	1650	7800	5'5"	25'7"	4.1	9.04
CE-TL-7-092-K	1700	9200	5'7"	30'2"	5.1	11.24
CE-TL-8-106-K	1750	10600	5'9"	34'9"	6.3	13.89
CE-TL-9-121-K	1800	12100	5'11"	39'8"	7.5	16.53
CE-TR-2-024-K	1380	2396	4'6"	7' 10"	1,22	2,69
CE-TR-3-035-K	1500	3571	4'11"	11' 9"	1,80	3,97
CE-TR-4-048-K	1620	4786	5'4"	15' 8"	2,50	5,51
CE-TR-5-060-K	1739	6042	5'8"	19' 10"	3,50	7,72
CE-TR-6-073-K	1859	7337	6'1"	24' 1"	4,50	9,92
CE-TR-7-086-K	1981	8671	6'6"	28' 5"	5,70	12,57
CE-TR-8-100-K	2033	9971	6'8"	32' 9"	6,60	14,55

Sicame North America

866 457 4830, info@sicamena.com
1675 Frontenac Road, Naperville, IL 60563

sicame
NORTH AMERICA